

**Global Titanium Inc****70% Ferrotitanium Fines (-10 Mesh)****Material Safety Data Sheet**

Revision Date: 3/9/11

Supersedes Date: 11/2/10

Page 1 of 5

**SECTION I. PRODUCT AND COMPANY IDENTIFICATION**

Chemical Name	Trade Name
<b>Ferrotitanium</b>	<b>70% Ferrotitanium Fines</b>
Chemical Family	Formula
<b>Group 4 (IVB) Transition Metal</b>	<b>FeTi</b>
Manufacturer	Manufacturer's Phone Number
<b>Global Titanium Inc.</b>	<b>(800) 762-7602 or (313) 366-5300</b>
Manufacturer's Address	Chemtrec Phone Number for Chemical Emergencies
<b>19300 Filer Ave Detroit, MI 48234</b>	<b>(800) 424-9300</b>
E-Mail	Company Website
<a href="mailto:info@globaltitanium.com">info@globaltitanium.com</a>	<a href="http://www.globaltitanium.com">www.globaltitanium.com</a>

**SECTION II. HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW**

Appearance & Odor	Warnings
<b>Silver/Gray Granular Solid; Odorless</b>	<b>Toxic or irritating gas may be produced in fire. Contact with water may result in explosion. May spontaneously combust. May explode in fire.</b>
OSHA Permissible Exposure Limit	ACGIH Threshold Limit Value
<b>15mg/m<sup>3</sup> (Total Dust); 5mg/m<sup>3</sup> (Resp. Dust)</b>	<b>10mg/m<sup>3</sup> (Total Dust)</b>
Carcinogens - OSHA, IARC, NTP	Medical Condition Aggravated by Exposure
<b>Not listed as a carcinogen under OSHA, IARC, or NTP.</b>	<b>May aggravate preexisting respiratory conditions.</b>
Potential Health Effects	Potential Environmental Effects
<b>May cause irritation. Toxic gas if exposed to heat.</b>	<b>No Information Available.</b>
Symptoms of Exposure	Target Organs
<b>May cause irritation.</b>	<b>Mucus Membranes</b>
Relevant route(s) of Exposure	
Inhalation <b>Yes</b>	Skin Contact <b>Yes</b>
Ingestion <b>Yes</b>	Eye Contact <b>Yes</b>

**While this material is not considered hazardous by the OSHA Hazard Communication Standard, this MSDS contains information critical to safe handling and proper use of this product. This MSDS should be retained and made available for employees and other users of this product.**

**SECTION III. COMPOSITION/INFORMATION ON INGREDIENTS**

Principal Components	C.A.S.#	% by Weight	TLV (ACGIH) mg/m <sup>3</sup>	PEL (OSHA) mg/m <sup>3</sup>
Titanium , Ti	7440-32-6	30-80	10.00	15.0(Total) 5.0(Respiratory)
Aluminum, Al	7429-90-5	0-10	10.0(Total) 5.0(Respiratory)	15.0(Total) 5.0(Respiratory)
Chromium, Cr	7440-47-3	0-2	0.5	1.0
Molybdenum, Mo	7439-98-7	0-4	NA	15.0
Iron, Fe	7439-89-6	15-60	NA	NA
Tin, Sn	7440-31-5	0-2	2.0	2.0
Vanadium, V	7440-62-2	0-10	NA	0.5(Dust) 0.1(fume)
Zirconium, Zr	7440-67-7	0-4	5.0	5.0
Nickel, Ni	7440-02-0	0-2	0.015	1.0

Global Titanium Inc

70% Ferrotitanium Fines (-10 Mesh)

## Material Safety Data Sheet

Revision Date: 3/9/11

Supersedes Date: 11/2/10

Page 2 of 5

### SECTION IV. FIRST AID MEASURES

Inhalation	Skin Contact
Remove from exposure to fresh air, restore or support breathing as needed. Seek medical assistance.	Flush skin with soap and water for at least 15 minutes, remove contaminated clothing.
Ingestion	Eye Contact
Do not induce vomiting. Seek medical assistance.	Flush with water for at least 15 minutes. If irritation persists, seek medical assistance.
Note to Physicians	
Treat systematically and supportively as required.	

### SECTION V. FIRE FIGHTING MEASURES

Flammable Properties
Product in itself is stable, but it will burn if introduced to fire. Fines and particulate matter are flammable and may spontaneously combust. Poisonous gases are produced in fire. Containers may explode in fire. Fire may reignite after extinguishing. Fire may produce significant heat.
Protection of Firefighters
Titanium fires produce intense heat. Wear self-contained breathing apparatus in pressure-demand, MSHA/NIOSH, and full protective gear. Irritating and highly toxic gases may be generated in fire.
Suitable Extinguishing Media
Class D fire extinguisher; table salt; sand; dry ground dolomite; or dry powder extinguishing agents. Do NOT use water directly on fire may result in explosion. Do NOT use carbon dioxide or halogenated extinguisher.
Special Fire Fighting Procedures
Small fires can be smothered with table salt, sand or by use of type D extinguishing material. For large fires allow the material, if contained, to burn out. If containment is not possible, call 911.
Unsuitable Extinguishing Media
DO NOT SPRAY WATER ON BURNING FERROTITANIUM. Water on molten or burning ferrotitanium may result in an explosion. Carbon Dioxide is NOT effective as an extinguisher. If moisture is present within burning metal fines an explosion may occur. Personnel should evacuate and not attempt to extinguish the fire.

### SECTION VI. ACCIDENTAL RELEASE MEASURES

Personal Precautions	
Use personal protective equipment recommended in Section VIII.	
Environmental Precautions	Methods for Containment
No information is available in regards to environmental hazards. Dispose of in accordance to local, state, and federal regulations.	Keep fines from becoming airborne. Do not use compressed air. If ferrotitanium fines become airborne, ventilate properly to reduce air density.
Methods for Cleanup	
Use non-sparking tools. Do not push powder long distances across the floor. Keep in small piles away from each other. Place material into non-sparking or anti-static containers. Use static-free vacuums for cleaning	
Other Information	
Spills of this material do not need to be reported to the National Response Center.	

### SECTION VII. HANDLING & STORAGE

Handling
Mixing, blending, milling or grinding of dry powder should be performed under argon or helium. Keep away from open flames and other sources of ignition.
Storage
Store indoors to maintain product integrity. Store away from excessive heat, welding, grinding, or torching operations. Use non-sparking/anti-static containers, tools, and equipment. Maintain a supply of coarse salt and/or Class D fire extinguisher near the processing and storage areas. Store in a cool, dry, well-ventilated area.

Global Titanium Inc

70% Ferrotitanium Fines (-10 Mesh)

# Material Safety Data Sheet

Revision Date: 3/9/11

Supersedes Date: 11/2/10

Page 3 of 5

## SECTION VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

OSHA PEL and ACGIH TLV have been set for ferrotitanium powder and dust only. OSHA PEL is 15mg/m<sup>3</sup> (Total Dust) and 5 mg/m<sup>3</sup> (Respiratory Dust). ACGIH TLV is 10 mg/m<sup>3</sup> (Total Dust). Not listed by IARC, NIOSH, NTP, or OSHA.

### Engineering Controls

Facility should be equipped with an eyewash and safety shower. Use adequate ventilation.

### Personal Protective Equipment

#### Eye/Face Protection

Safety glasses with permanent side shields or goggles.

Contact lenses may pose a hazard.

#### Respiratory Protection

Follow the OSHA respirator regulations found in 29CFR 1910.134 or European Standard EN149. Use approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

#### Skin Protection

Leather or puncture resistant gloves. Wear appropriate clothing to prevent skin exposure.

#### General Hygiene Considerations

Wash hands after handling. Wear recommended PPE. Contact lenses may absorb irritants. Avoid transfer of material from hands to mouth while eating, drinking, or smoking.

## SECTION IX. PHYSICAL AND CHEMICAL PROPERTIES

### Appearance

Silver/gray metal; Solid

### pH

N/A

### Flash Point

Ingot/solid pieces will not flash.

### Evaporation Rate

N/A

### Viscosity

N/A

### Auto-Ignition Temperature

N/A

### Odor/Odor Threshold

Odorless

### Melting Point

1100-1600°C

### Upper Explosive Limit

N/A

### Vapor Pressure

Not volatile

### Solubility

Insoluble

### Auto-Ignition Temperature

N/A

### Physical State

Solid

### Boiling Point

>3000°C

### Lower Explosive Limit

N/A

### Vapor Density

N/A

### Specific Gravity

~5.6-6.8

### Decomposition Temperature

N/A

## SECTION X. STABILITY AND REACTIVITY

### Chemical Stability

Stable

### Conditions to Avoid

Keep away from sparks and flames, incompatible materials, and strong oxidants.

### Incompatible Materials

Reacts with strong acids, aluminum, halogens, interhalogens, oxygen, chlorinated solvents, carbon dioxide, oxidizing agents, bromine trifluoride, nitric acid, silver fluoride, sodium chlorate, halocarbons, and metal oxides.

### Hazardous Decomposition Products

Irritating and toxic fumes and gases, titanium oxide, metallic oxides, and dust.

### Possibility of Hazardous Reactions

May react violently with interhalogens, oxidizing agents, strong acids or halogenated compounds. Reactions with incompatible materials may result in irritating or toxic gas. Fines are spontaneously flammable in air.

Global Titanium Inc

# Material Safety Data Sheet

Revision Date: 3/9/11

Supersedes Date: 11/2/10

Page 4 of 5

## SECTION XI. TOXICOLOGY INFORMATION

ACUTE EFFECTS	CHRONIC EFFECTS
Oral May cause irritation of the digestive tract. Poorly absorbed from the alimentary tract.	Carcinogenicity Tumorigenic effects have been observed in experiments with laboratory animals.
Dermal Irritant to skin and mucous membranes.	Mutagenicity Properties have not been thoroughly evaluated.
Inhalation May cause irritation, pneumoconiosis, and other respiratory conditions.	Reproductive Effects Properties have not been thoroughly evaluated.
Eyes May cause irritation, conjunctivitis, and other ocular conditions.	Developmental Effects Properties have not been thoroughly evaluated.
Other No other acute effects have been noted.	Sensitization Sensitization is not believed to occur.

## SECTION XII. ECOLOGICAL INFORMATION

Ecotoxicity No information was available regarding the toxicological effects on the environment.	Persistence/Degradability No information was available regarding the environmental degradation of this product.
Bioaccumulation/Accumulation No information was available regarding the ability of this product to bioaccumulate.	Mobility in Environmental Media No information was available regarding the mobility of this product in the environment.
Other Adverse Effects No information available.	

## SECTION XIII. DISPOSAL CONSIDERATIONS

Disposal Dispose according to local, state, and federal regulations.
---

## SECTION XIV. TRANSPORTATION INFORMATION

Proper Shipping Description 70% Ferrotitanium Fines (-10 Mesh), not a DOT regulated material
---

## SECTION XV. REGULATORY INFORMATION

Section 313 Supplier Notification: This product contains the following chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 (40 CFR 372): Aluminum (dust/fume) C.A.S. 7429-90-5, Chromium C.A.S. 7440-47-3, Nickel C.A.S. 7440-02-0, and Vanadium (exempt when contained in alloy) C.A.S. 7440-62-2.

In addition to the ingredients listed II, this product contains the following chemicals considered by the State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as causing cancer or reproductive toxicity and for which warnings are now required: Nickel C.A.S. 7440-02-0 Listed Carcinogen.

The Comprehensive Environmental Response, Compensation, and Liability Act of 1990, Sec102 (CERCLA) requires that any "release" into the "environment" of these hazardous substances contained in a product in excess of the "reportable quantity" in any 24-hour period must be immediately reported to the National Response Center (800-424-8802). Reporting is not required under certain circumstances such as a federally permitted release or the release of certain metal solid particles with a diameter larger than 100 micrometers: Chromium and Compounds, 0-18% by weight, Reportable Quantity: 5,000lb and Nickel, 0-2% by weight, Reportable Quantity: 100lb.

The Superfund Amendments and Reauthorization Act of 1986 (SARA) specifies certain emergency planning and notification requirements if these extremely hazardous substances are present in concentrations of greater than 1% at a facility in amounts greater than the threshold planning quantity: To the best of our knowledge, this product does not contain materials listed as EHS under SARA

**70% Ferrotitanium Fines (-10 Mesh)**

# Material Safety Data Sheet

Revision Date: 3/9/11

Supersedes Date: 11/2/10

Page 5 of 5

## SECTION XV. REGULATORY INFORMATION CONTINUED

If this product is discarded as a waste, it would be identified with the following hazardous waste classification under the Resource Conservation and Recovery Act (RCRA). The act specifies requirements for the management and disposal of hazardous wastes: To the best of our knowledge, this product is not classified as hazardous waste under RCRA.

Canada - Components on Canadian "Ingredient Disclosure List": Aluminum, elemental; Chromium, elemental; Molybdenum, elemental; Tin, elemental; Vanadium, elemental; Nickel, elemental; and Zirconium, elemental.

DSL/NDSL: Titanium is listed on Canada's DSL List.

WHMIS: Classification B4, B6

Toxic Substances Control Act (TSCA): Components of this product listed on the TSCA Inventory are: Aluminum (C.A.S.7429-90-5); Chromium (C.A.S.7440-47-3); Molybdenum (C.A.S.7439-98-7); Silicon (C.A.S. 7440-21-3); Nickel (C.A.S. 7440-02-0); Tin (C.A.S.7440-31-5); Titanium (C.A.S.7440-32-6); Vanadium (C.A.S. 7440-62-2); Zirconium (C.A.S. 7440-67-7); Niobium (C.A.S. 7440-03-1).

Clean Air Act (CAA): To the best of our knowledge, this product does not contain hazardous air pollutants or Class 1 or Class 2 Ozone depleters as defined by the CAA.

Clean Water Act (CWA): To the best of our knowledge, this product does not contain hazardous substances, priority pollutants, or toxic pollutants as defined by the CWA.

## SECTION XVI. ADDITIONAL INFORMATION

The information provided in this document is believed to be accurate, but does not purport to be all inclusive and shall be used for reference purposes only. We make no warranty of merchantability or any other warranty, expressed or implied, with respect to such information and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Global Titanium be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential, or exemplary damages, howsoever arising, even if Global Titanium has been advised of the possibility of such damages.